

LINE ITEM 4 SPECIFICATION

1A. GENERAL ASSEMBLY

THE COMPLETE TRUCK MOUNTED ATTENUATOR (TMA) SHALL BE DESIGNED TO MAKE ATTACHMENT TO A VARIETY OF SUPPORT VEHICLES AND BE RAISED AND LOWERED FROM INSIDE THE CAB OF THE SUPPORT VEHICLE. MAJOR COMPONENTS (LISTED BELOW) STAY TOGETHER WHEN DETACHED FROM THE SUPPORT VEHICLE. THE TRUCK MOUNTED ATTENUATOR MUST BE CAPABLE OF BEING MOUNTED TO A VARIETY OF VEHICLES WITH SIZES RANGING FROM 13,500 GVW TO 25,000 GVW AND STILL MEET ALL MASH-2016 TESTS OUTLINED BELOW. THE TMA FRAME SHALL BE CAPABLE OF COLLAPSING WHEN IMPACTED BY AN ERRANT VEHICLE. NO PORTION OF THE TMA SHALL PROTRUDE FORWARD UNDER THE TRUCK DAMAGING ITS VITAL ELEMENTS DURING AN IMPACT.

THE TMA SYSTEM MUST BE DELIVERED ASSEMBLED AND READY FOR ATTACHMENT TO SUPPORT VEHICLE. STANDARD MOUNTING HARDWARE THAT WAS USED IN CRASH TESTING CERTIFICATION SHALL BE PROVIDED WITH ATTENUATOR.

1B. MAJOR COMPONENTS

THE TRUCK MOUNTED ATTENUATOR WILL CONSIST OF THE FOLLOWING MAJOR COMPONENTS:

- 1- STEEL BACKUP FOR ATTACHMENT TO HOST VEHICLE W/ SUPPORT STRUCTURE
- 2- CURVED ALUMINUM TUBE FRAMES
- 3- FOUR (4) ALUMINUM ENERGY ABSORBING MODULES
- 4- HYDRAULIC SYSTEM CAPABLE OF RAISING THE SYSTEM SO THAT THE REAR SECTION RESTS HORIZONTALLY OVER THE BED OF THE HOST VEHICLE

1C. MINIMUM WEIGHT AND DIMENSIONS

LENGTH- 12'- 10"

WIDTH- 96"

HEIGHT- 36"

WEIGHT- 1,975LBS

1D. CRASH TESTING CRITERIA

THE TMA SHALL HAVE BEEN TESTED TO, AND SUCCESSFULLY PASSED ALL 4 TESTS THAT FALL UNDER THE GUIDELINES OF MASH-2016 TEST LEVEL 3 FOR TRUCK MOUNTED ATTENUATORS.

1E. LIGHTING AND VISIBILITY

THE TMA SHALL HAVE A LIGHTING ASSEMBLY PER FMVSS NO. 108 LAMPS, REFLECTIVE DEVICES, AND ASSOCIATED EQUIPMENT. ALL COMPONENTS SHALL BE APPROPRIATE FOR THEIR INTENDED PURPOSE UNDER ANY ADOPTIONS ISSUED BY THE NHTSA, SAE AND FMVSS. THIS IS STANDARD PRACTICE FOR ELECTRICAL LIGHTING. THE TMA SHALL INCLUDE BRAKE LIGHTS, TAILLIGHTS, TURN SIGNALS AND AN ICC BAR LIGHT. WIRES SHALL BE ROUTED IN A PROTECTIVE, JACKETED CABLE. MOLDED CONNECTORS SHALL BE USED WHERE INDIVIDUAL WIRES WOULD OTHERWISE BE EXPOSED TO THE ELEMENTS. A STANDARD, SINGLE, 7 PIN TRAILER CONNECTOR SHALL MAKE THE CONNECTION FOR ALL LIGHTS TO THE BACK OF THE TRUCK.

THE SURFACE OF THE IMPACT FRAME FACING ONCOMING TRAFFIC SHALL DISPLAY A BLACK ON YELLOW INVERTED CHEVRON PATTERN WITH 4 IN. WIDE COLOR BANDS. THE COLORS SHALL MEET THE VALUE AND TOLERANCE LIMITS ESTABLISHED BY MUTCD.

1F. ACCEPTABLE BRANDS/MODELS

SCORPION II ATTENUATOR BY TRAFFIX DEVICES, INC OR EQUAL